



# WAX-RESIN

For Near Edge Printers

## Recommending a ribbon

What is the application?

What is the label stock and how wide is it?

What level of durability is required?

What thermal printer is being used?

# NETMark

Premium Wax-Resin. Productivity and durability.

When the risk of a printing interruption threatens the continuity of your production, you need a ribbon that offers endless reliability and top quality output. Netmark has proven itself time and time again. Although widely used for inline applications, Netmark performs well across all near edge printing systems.

Netmark offers outstanding performance at high printing speeds. It delivers exceptional print quality and mechanical resistance on a variety of in-line and auto ID applications.

The anti-static properties of Netmark make it an ideal choice for RFID overprint applications. ISEGA approval of Netmark guarantees safe use for food packaging applications.

## Benefits

- Excellent scratch and smudge resistance
- Broad stock latitude
- Quick and reliable printing
- Anti-static for increased print head protection.

## Applications

- Flexible packaging
- General purpose
- Shipping, warehousing, and receiving
- Shelf and bin
- Retail tag and label
- Textile and apparel ticket
- Compliance

## Technical Specifications

Colour Code Tab .....Silver

Maximum Print Speed ... 24 IPS

Film Thickness ..... 4.5 μ

Total Ribbon Thickness ... 7 μ

Transmission Density .....0.80  
MacBeth Scale

Ink Melting Point.....70°C

Storage Condition  
-5 ° to 40 ° C  
20 % to 85 % Humidity

## Sample NETMark Ribbons

Part # CES055MXK –  
55mm x 100m – CSI - Markem  
Part # CES110MXC –  
110mm x 50m – CSI – Novexx  
Part # CES106MX –  
106mm x 50m – CSO – TEC BX  
Part # CES220M8 –  
220mm x 50m – CSO – TEC B872

## Performance

